

型号 Item No.	E-500	E-650	E-8070	E-1080	E-1280	E-1311
工作台 / Worktable						
工作台尺寸(mm) Worktable Size	450*500	500*600	690*800	820*1020	820*1200	1000*1300
最大载重(kg) Max. loading capacity	200	300	400	900	900	800
行程 / Travel						
三轴行程(mm) Three-axis travel	450*500*200	500*600*280	700*800*350	800*1200*350	820*1200*350	1100*1300*520
龙门可通过工作最大高度(mm) The maximum work height of gantry	350/450	380/480	480	480	480	600
主轴 / Spindle						
主轴弹簧夹头 Spindle	ER20/ER25	ER25/ER32/BT30	ER25/ER32/BT30	ER25/ER32/BT30	ER25/ER32/BT30	BT40
主轴转速范围(r/min) Spindle speed range	3000~24000	3000~24000	3000~18000	3000~18000	3000~18000	8000~12000
主轴马达 (KW) Spindle Motor	2.2~4.0	2.2~5.5	5.5~7.5	5.5~7.5	7.5	7.5/11
进给 / Feed						
快速移动速度(mm/min) Rapid moving speed	10000	10000	15000	18000	18000	15000
最高切削速度(mm/min) Max. cutting speed	10000	10000	15000	18000	18000	15000
精度 / Accuracy						
定位精度(mm) Positioning accuracy	± 0.005	± 0.005	± 0.005	± 0.005	± 0.008	± 0.01
重复定位精度(mm) Repeatability	± 0.0025	± 0.0025	± 0.0025	± 0.0025	± 0.004	± 0.005
机床尺寸重量 / Dimension & Weight						
外观尺寸(mm) Dimension	1750*1670*2000	1800*1900*2200	2350*1900*2400	3000*2400*2600	3200*2400*2650	3800*2100*2600
机械重量(T) Weight	2.5T	3T	4T	6T	6.8T	9.5T
其它 / Others						
切削液系统 Cutting fluid system	双喷头 (切削液、压缩空气) Double nozzle (cutting fluid, compressed air)					
润滑系统 Lubrication system	自动润滑系统 (68号导轨油) Self-lubrication system (NO.68 Rail Oil)					
电源及总功率 Power supply and total power	三相交流380V 4.0~7.5~15KW Three phase AC 380V 4.0~7.5~15KW					